


ВЫСОКОТЕМПЕРАТУРНЫЕ ИСТОЧНИКИ ТОКА



Feature

- Extreme Shock & Vibration Resistance
- Available Temperature 150°C ~ 200°C
- Very High Power and Energy Density
- High and Stable Operating Voltage

Applications

- MWD(Measurement While Drilling)
- LWD(Logging While Drilling)
- Cased-Hole Logging

Packing Information

Model	Cell weight(kg)	Packing qty per Case	Netweight per Case(kg)	Grossweight per Case(kg)	C/TSize
DD-HR-150G	0.23	64	14.72	15.82	427mm x 302mm x 210mm
DD-HR-150A	0.23	64	14.72	15.82	
DD-MR-165	0.225	64	14.4	15.5	
DD-MR-180	0.225	64	14.4	15.5	
CC-MR 165(21mm)	0.08	100	8.0	9.1	
CC-MR 165(25mm)	0.115	80	9.2	10.3	
CC-MR 165(26mm)	0.12	80	9.6	10.7	
SC-DD01 (PIG-DD)	0.213	64	13.63	14.73	
FAT-D-150	0.337	36	12.13	13.13	450mm x 250mm x 230mm
SC-D01 (PIG-D)	0.122	80	9.76	10.76	
SC-C01 (PIG-C)	0.059	150	8.85	9.85	