



LITHIUM PRIMARY BATTERY

Technical List

Packing Information

Type	Model	Unit/Packing	Net Wt. (g)	Inner Box		Outer Box				
				Q' ty(pcs)	Net Wt.(g)	Q' ty(pcs)	Net Wt.(kg)	Gross Wt. (kg)	CBM	Dimension(mm)
Li/SOCL ₂ Bobbin type	SB-AA02(P)	1pc.(bulk)/TC,ST,P	9.2	100	980	1000	9.8	10.7	0.0337	510×330×200
		1pc.(bulk)/AX	9.2	30	316	300	3.2	4.1	0.0290	435×370×180
	SB-AA11(P)	1pc.(bulk)/TC,ST,P	16.0	100	1660	600	10.0	10.9	0.0337	510×330×200
		1pc.(bulk)/AX	16.0	25	440	250	4.4	5.3	0.0290	435×370×180
	SB-A01	1pc.(bulk)/TC,ST,P	24.0	90	2220	540	13.3	14.2	0.0337	510×330×200
	SB-C02	1pc.(bulk)/TC,ST,P	51.0	50	2610	300	15.7	16.6	0.0357	515×347×200
	SB-D02	1pc.(bulk)/TC,ST,P	100.0	30	3060	120	12.2	13.1	0.0337	510×330×200
Li/SOCL ₂ Spiral type	SW-AA01	1pc.(bulk)/TC,ST,P	9.2	100	980	1000	9.8	10.7	0.0337	510×330×200
	SW-AA11	1pc.(bulk)/TC,ST,P	17.0	100	1760	600	10.6	11.5	0.0337	510×330×200
	SW-A01	1pc.(bulk)/TC,ST,P	30.0	90	2775	540	16.7	17.6	0.0337	510×330×200
	SW-C01	1pc.(bulk)/TC,ST,P	51.0	50	2610	300	15.7	16.6	0.0357	515×347×200
	SW-D02	1pc.(bulk)/TC,ST,P	102.0	30	3120	120	12.5	13.4	0.0337	510×330×200
	BW-D01	1pc.(bulk)/TC,ST,P	102.0	30	3120	120	12.5	13.4	0.0337	510×330×200
	CR123A	1pc.(Blister)	16.0	10	210	200	4.7	5.3	0.0202	509×228×174
	CR-2	1pc.(Bulk)	11.5	100	1,649	800	13.2	14.0	0.0202	509×228×174
		1pc.(Blister)		10	159	200	3.7	4.3	0.0202	509×228×174
1pc.(Bulk)		40		539	960	12.9	13.7	0.0202	509×228×174	

